



Office of the General Manager (S&T) E.C. Railway/HJP

No.- ECR/S&T/JPO/185-A/Part-II

Dtaed-19.10.2023

Divisional Railway Manager/DHN, DNR, DDU, SEE & SPJ East Central Railway

Sub: - JPO for Disconnection/Reconnection of S&T gears during regular maintenance and during rectification of failures.

Please find enclosed herewith, Joint Procedure Order No. ECR-HQ/S&T/Sig./JPO/185-A/Pt.-II dated 19.10.2023 regarding Disconnection/Reconnection of S&T gears during regular maintenance and rectification of failures, duly signed by PCSTE and PCOM.

It is requested to kindly get the JPO implemented in your Division.

DA: As above

ศ[///]/4||0[// (Niraj Yadav) CSTE/D&D

Copy to:

PCOM/ECR for kind information please.

CSTE/Works/HJP for kind information & necessary action please.

CSTE/Con/North & South/MHX for kind information & necessary action please.



East Central Railway

No. ECR-HQ/S&T/Sig/JPO//85.A /Pt. []

Date: 19.10.2023

JPO for Disconnection/Reconnection of S&T gears during regular maintenance and during rectification of failures

1.	Pla	nning for signal maintenance:	Action D
 '	1.1		Action By
	'-'	Day-wise requirement of disconnections with tentative duration shall be worked out in advance, on weekly basis, and submitted to Operating at	Division Optg.
	ĺ	Divisional level to be incorporated in the rolling block program. During	& S&T Teams
		the weekly review, care must be taken that no signaling gears become	
		overdue for maintenance. While working out the tentative duration care	
		must be taken to also include all related activities so as to avoid block	
	1	burst.	
2.	Dis	connection/Reconnection during maintenance activities :	
	2.1	SSE/JE/Technician shall present Disconnection memo to SM as per	Station Optg.
		requirement under intimation to signal control mentioning time from	& S&T Teams
		when required and tentative duration of disconnection.	
	2.2	On receipt of Disconnection Notice, SM will advise CNL and obtain	1
		permission for Disconnection along with duration under exchange of	
		private No. from CNL. If train running does not permit Disconnection at	
		that time, next probable time to will be intimated by SM as advised by	1
		CNL. Entries will be made by SM at appropriate place on	
	2.3	acknowledgement foil of form No S&T/DN.	
	2.3	If the maintenance work includes any wiring modifications like re-jointing	
		of cables, rewiring of Signaling gears, re-termination of cables at terminals/relay contacts, etc. Correspondence test shall be conducted	
		before issue of Reconnection Notice.	
	2.4	Correspondence test : SSE/JE/Technician shall contact ASM/SS on	
		duty at Panel/VDU, tell him status of concerned gear(s) at site, seek	
		indication/status of the corresponding gear(s) on his Panel/VDU and ask	
		for operation of gears to be tested as per requirement. SM shall clearly	
		advise SSE/JE/Technician at site about the state of the gear(s) on his	
		panel/VDU and operate gears from Panel/VDU as per the requirement of	
İ		SSE/JE/Technician at site.	
	2.5	After completing Correspondence tests as above, SSE/JE/Technician	
į		should issue Reconnection Notice on form No S&T Disconnection	. •
- 1	.	with endorsement that correspondence testing has been done. SSE/JE/Technician & SM/SS then shall make all necessary	
	i	The state of the s	
		entries/remarks in Acknowledgement part of form No S&T	
ļ		Disconnection and also in corresponding Disconnection/Re-connection registers maintained by S&T and Operating, respectively.	
3.	Disc	onnection/Reconnection during attending Signaling failures :	
+	3.1		<u> </u>
	J. 1	Before taking up any work, SSE/JE/Technician shall first seek failure memo from SM/ASM in accordance with provision of SR 3.68(1)(v) for	Station Optg.
		each failure recorded in the signal failure register and then depending	& S&T Teams
		upon requirement shall issue Disconnection Notice which shall be	
].	accepted by SM to facilitate timely rectification of failure.	,
	L	The state of the s	

....2/-

- DUDAN

range.



a management of the state of th	3.2	After rectification of the failure, if the works done for rectification of the failure involving works mentioned in para 2.3 above, correspondence test as per para 2.4 & making necessary entries as per para 2.5 should be completed. Whether the failure required Disconnection Notice or not, SSE/JE/Technician shall make necessary entries in SFR by giving cause of failure, date & time of rectification and put his signature with name & designation.	& S&T
4.	Tra	n operation after maintenance/signal failure :	
	4.1	After completion of work. SM will operate trains on signals only on receipt of Reconnection Notice. Thereafter, the first train to pass on Main Line should be dealt as under:-	Station Operating staff
		 The reception of the first train should NOT be on green aspect of first stop signal. 	
		b) The departure signal for run through trains should be taken off once the train has occupied the berthing portion by seeing the relevant indications on panel/VDU.	
		c) This should be applicable for all Up and Down direction trains. d) Exception to these instructions will be in case of stations where reception or reception and departure signals are kept in "Off" position to avoid stalling of loads due to rising gradients or site conditions. Necessary instructions may be incorporated in working rules to admit these trains into the yard at restricted speed by keeping the departure signal "On".	

(Eknath Mohker)
PCSTE/ECR

(Dr. Mano) Singh PCOM/ECR