


ASPECT CONTROL CHART DN



ASPECT CONTROL CHART UP





PANEL DETAIL

MAIN SIGNAL :-1,2,3,4,A,6,8,10,11,12,13,14,15,16,17,21,23,24.
DISTANT SIGNAL :-1,2,3,4,5,6,7,8,9,10.
SHUNT SIGNAL:186,188,190,192,194,196,198,200,202,204,206,208,209,211.
POINTS :- 51,52,53,54,55,56,57,58,59,60,61,64,65,66,67,68,69.
CRANK HANDLE CONTROL BUTTONS:-CB-1,CB-2,CB-3,CB-4,CB-5,CB-6,CB-7,CB-8,CB9.

NOTE

1. ABSOLUTE BLOCK SYSTEM OF WORKING WITH STATION: DHANBAD, BALLI JN. & GOMOH.
2. R.R.TYPE TER (DIAG) SIGNAL WITH STATION BALLI JN & GOMOH AND TELE BLOCK INSTRUMENT WITH DHANBAD SITUATED IN PANEL ROOM.
3. CONTROL TELEPHONE IS PROVIDED IN S&T'S OFFICE (PANEL ROOM).
4. BLOCK PROVING AXLE COUNTER IS PROVIDED WITH ADJACENT STATION: DHANBAD, BALLI JN. & GOMOH ON BOTH SIDE. THESE SHOULD BE INTERLOCKED WITH BLOCK INSTT.
5. ALL ANGLE OF CROSSINGS ARE 1IN 12 EXCEPT INDICATED.
6. ALL TURNOUTS ARE ON 52 KG 90 UTS PSC SLEEPER BASE. JOINTS OF THE REPLACEMENT TRACK IS TO BE PROVIDED AT LEAST ONE RAIL LENGTH IN ADVANCE OF THE CORRESPONDING SIGNALS.
7. STAGGERING OF INSULATION BLOCK JOINTS OF TRACK CIRCUIT 1T-2T,3T-4T & 2TT-3ST BY 1.82 M.

SPECIAL INSTRUCTION / APPROVED SPECIAL INSTRUCTIONS

SL NO.	INSTRUCTIONS	ISSUED BY	AUTHORITY	DATE	REMARKS
1.		C.R.S.	SE/T/C/E.RLY. P/U/SIG/ms/Instr	16.05.08.	

SIGNATURE OF SSE/SIG/DHN

ALT	DESCRIPTION	REFERENCE	DATE	CHECKED BY	CONSTRUCTED BY	SIGNATURE

| | | | | | |